

Datasheet


www.vitrum.com

Vitrum I BS On/Off Wireless

cod. 01B010020







CE

FUNCTIONAL SPECIFICATION

- One-button light switch
- Touch control with capacitive technology and concave surface for tactile Feedback
- Acoustic feedback signal
- Crown backlit by low-consumption LEDs

COMMAND MODE

One capacitive button with "On-Off" contol

MECHANICAL CHARACTERISTICS

- Box British 1 Gang (wall or plasterboard)
- Dimension 95x95mm
- Depht at sight 8 mm
- Operating temperature: 0-40°C
- Button Diameter 38 mm
- Light ring diameter 42 mm
- Weight: 200 g.

ELECTRICAL CHARACTERISTICS

- Power: 230Vac
- Energy consumption: < 1W
- Configuration: 3 wires
- Relay 16 A (P.F.=1)
- Output power per channel "< 2400 VA"
- Control of following lamp:
 - incandenscent
 - halogenal
- For loads < 1500 VA for the control of:
 - Electronic or Electromechanical transformer
 - Fluorescent Linear Tubes
- Frequency of communication: F.M. 868.4MHz R.F radiated power <1mW
- R.F. Range: 20 m. MAX (open field)

Compliant with:

B.T.: 2006/95/CE E.M.C.: 2004/108/CE **R&TTE:** 1999/5/CE