

# Datasheet


www.vitrum.com

# Vitrum I EU Satellite Wireless

# cod. 01E010030

SPEAKS 🗷 WAVE





CE

#### **FUNCTIONAL SPECIFICATION**

- One-button light switch
- Touch control with capacitive technology and concave surface for tactile Feedback
- Acoustic feedback signal
- Crown backlit by low-consumption LEDs

#### **COMMAND MODE**

- One capacitive button with "On-Off" contol .
- Dimming touch: .
- Single short pressure for "On-Off"
- Keeping pressure: light increase from 0 to 100% .
- Dimmering by circular touch (iPOD like control) (increasing with clockwise touch, decreasing with counterclockwise touch)

## **MECHANICAL CHARACTERISTICS**

- Fitting Box 503 (wall or plasterboard) .
- Dimension 126x95mm
- Depht at sight 8 mm .
- Operating temperature: 0-40°C .
- Button Diameter 38 mm
- . Light ring diameter 42 mm
- Weight: 190 g. .



- Power: 230V ac
- Energy consumption: < 1W
- Frequency of communication: F.M. 868.4MHz R.F radiated power <1mW • •
  - R.F. Range: 20 m. MAX (open field)

Compliant with:

E.M.C.: 2004/108/CE R&TTE: 1999/5/CE



Think Simple SpA reserves the right to modify its products at any time and without notice in order to better their quality and functionality. Therefore, all the information given in this datasheet is to be considered subject to possible modifications.

Think Simple SpA

CF / P.Iva 01675770935 www.thinksimple.it info@thinksimple.it support@thinksimple.it

#### Head Office

viale Lino Zanussi, 3 33170 Pordenone Tel +39 0434 516 216 Fax +39 0434 516 230

### **Sales Office**

corso Garibaldi, 86 20121 Milano Tel +39 02 655 600 29 Fax +39 02 454 982 95